



PRODUCT PERFORMANCE REPORT

Document ID 1548141365
 Issued on January 22nd, 2019

PROJECT IDENTIFICATION - This product performance report is delivered for:

Name **Roman Salomoun**
 Company **JABLOTRON LIVING TECHNOLOGY s.r.o.**
 Project reference **CoolBreeze**
 Project location **Czech Republic**

PRODUCT IDENTIFICATION

Certification Diploma N° **94.01.198**
 Brand **FUJITSU**
 Range **ASY**L**
 Product type **Comfort Air Conditioners / up to 12 kW / Air cooled / Split / Reverse cycle**
 Product reference **AOYG07LUCA / ASYG07LUCA**

Important notice:

- I. Data featured in this report are valid at the date of issue. The scope of this product performance report does not include all certified data that can be checked at <http://www.eurovent-certification.com>
- II. This product performance report is valid only for above product features and should not be referred to as a Diploma.

FEATURE	VALUE	UNIT
Acoustic		
LwO env	58	dB(A)
LwI1 env	57	dB(A)
Bivalent Point		
Tbiv	-7	Å,Å°C
Ph TBiv	2.3	kW
COP @ Tbiv	2.8	
Cooling PL CondB		
Pc Stage 1 @ 30°C	1.47	kW
EER Stage1 @ 30°C	7.37	
Cooling PL CondC		
Pc Stage 1 @ 25°C	1.51	kW
EER Stage1 @ 25°C	10.38	
Cooling PL CondD		
Pc Stage 1 @ 20°C	1.62	kW
EER Stage1 @ 20°C	13.67	
General		
Mounting	Wall mounted	
MPS	230-1-50	
Refrigerant	R410A	
Refr. Line	5,0 m	m
Heating 14511		
Ph @+7	3	kW



PRODUCT PERFORMANCE REPORT

Document ID 1548141365
Issued on January 22nd, 2019

FEATURE	VALUE	UNIT
COP @+7	4.05	
Heating Average Climate		
Pdesignh	2.6	kW
SCOP	4.02	
SCOP Class	A+	
Qhe	887	kWh/annum
Heating PL Conda		
Ph Stage1 @ -7°C	2.3	kW
COP @-7°C	2.53	
Heating PL CondB		
Ph Stage 1 @ +2°C	1.4	kW
COP Stage 1 @ 2°C	3.95	
Heating PL CondC		
Ph Stage 1 @ +7°C	1.31	kW
COP Stage1 @ +7°C	6.03	
Heating PL CondD		
Ph Stage1 @ +12°C	1.49	kW
COP Stage 1 @ +12°C	6.68	
Poffc		
Poff	G	W
Poffh		
Poffh	11	W
Ptoc		
Pto	5	W
Seasonal Efficiency in Cooling		
Pdesignc	2	kW
SEER	7.2	
SEER Class	A++	
Qce	97	kWh/annum
Thermal		
Pc	2	kW
EER @+35	4.35	
TOL Runing Test		
TOL	-15	Å,Å°C
Ph @ TOL	1.69	kW
COP @ TOL	2.4	